
Samsung LH65QMCEBGCXGO pantalla de señalización Pantalla plana de señalización digital 165.1 cm (65") LCD Wifi 500 cd / m² 4K Ultra HD Procesador incorporado Tizen 24/7

Marca : Samsung Código del producto: LH65QMCEBGCXGO

Nombre del producto: LH65QMCEBGCXGO







Display		Design	
Panel type VA Display diagonal * 165.1 cm (65")	165.1 cm (65")	Anti-glare screen Mounting type	✓ Wall
Display technology * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio	3840 x 2160 pixels shtness * 500 cd/m² 4K Ultra HD n *	Performance Purpose * Multi-display supported Multicast support Operating hours (hours/days)	Commercial ✓ 24/7
Response time Contrast ratio (typical) Dynamic contrast ratio marketing name		HDCP International Protection (IP) code HDCP version	✓ IP5X 2.2
Viewing angle, horizontal 178° Viewing angle, vertical 178° Display number of colours 1 billion colours Pixel pitch 0.372 x 0.372 mm Active display area (W x H) 1428.48 x 803.52 mm Number of displays 1	178° 1 billion colours 0.372 x 0.372 mm	Power Power consumption (typical) * Power consumption (standby) * Power consumption (sleep) AC input voltage AC input frequency	187 W 0.5 W 0.5 W 100 - 240 V 50 / 60 Hz
Colour saturation Horizontal scan range Vertical scan range Haze rate	72% 30 - 81 kHz 48 - 75 Hz 25%	Computer system Computer system * Computer system type Built-in processor *	System on Chip (SoC)
Ports & interfaces HDMI ports quantity * HDMI version HDMI input ports quantity	3 2.0 3	Processor frequency Internal storage capacity Operating system installed Operating system version	1.6 GHz 16 GB Tizen 7.0
DVI port * DisplayPorts quantity * DisplayPorts in USB port * USB ports quantity	x 1 1 • 2	Weight & dimensions Display width Display depth Display height Display weight	1456.8 mm 28.5 mm 831.9 mm 21.2 kg
USB version Ethernet LAN *	2.0	Packaging data Package weight	28.6 kg

Ports & interfaces		Packaging content	
Ethernet LAN (RJ-45) ports	1	Remote control included	1
Wi-Fi *	✓	Batteries included	✓
Audio (L/R) out	1	Cables included	RS-232
RS-232 interface	✓	Operational conditions	
Infrared data port	✓	Operating temperature (T-T)	0 - 40 °C
Audio		Operating relative humidity (H-H)	10 - 80%
Built-in speaker(s) *	✓	Certificates	
Number of built-in speakers	2	Certification	EMC Class B
RMS rated power	10 W	Features	
Design		Wall mountable	1
Product design * Placement supported *	Digital signage flat panel Indoor	Technical details	
Orientation Horizontal/Vertical VESA mounting * Panel mounting interface 400 x 300 mm Bezel width (bottom) 1.15 cm Bezel width (side) 1.15 cm Bezel width (top) 1.15 cm	✓ 400 x 300 mm 1.15 cm 1.15 cm	Special features	Signage new home workspace (Microsoft371/VMWare/RDP), custom home auto, source switching and recovery, dicom simulation mode, director mode, SmartView+, upgradable webengine, Tizen enterprise platform, video conference solution, smart calibration
		Sustainability certificates	ENERGY STAR, EPEAT Bronze

